



- ◆SPECIFICATIONS
- Current rating: 0.4A AC, DC
 - Voltage rating: 50V AC,DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 100MΩ Min.
 - Withstanding voltage: 250V AC/ minute.
 - Contact resistance: 30mΩ Max.

Material:

- Insulator: LCP UL 94V-0
- Actuator: LCP
- Contact: Phosphor Bronze
- Peg: Phosphor Bronze
- Plating: Tin plated over Nickel
- Circuits: 4~60

$A = 0.50 * (\text{circuit} - 1)$
 $B = A + 1.10$
 $C = A + 6.50$
 $D = A + 7.20$

*Available in 4 through 60 circuits

F	④				GENERAL TOLERANCE		UNIT: mm	DATE	TITLE:		 东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.	F	
	③				.X±0.20	X°±1°	DRAWN: 闵昕皓	2015.04.30	0.5mm pitch 2.0H 卧式半包上接				
	②				.XX±0.10	.X°±	CHECKED:		VER.	SCALE:			N/A
	①				.XXX±0.05	.XX°±	APPROVED: 周志龙	2015.04.30	A	SHEET:			1/1
	LTR	NAME	DATE	VERISION RECORD							PROJECTION	PART NO.	F0500120DxxSD110
												DRAWING NO.	F0500WHS04-1-S