





RoHS
COMPLIANT

◆ SPECIFICATIONS

- Current rating: 2A AC, DC
- Voltage rating: 250V AC,DC
- Temperature range: -40°C ~ +105°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 800V AC/ minute.
- Contact resistance: 20mΩ Max.

Material: Nylon 66 UL 94V-0



Recommended P.C.Board Layout

PART No.	Dimension mm	
	A	B
H2003R1020101A	2.00	5.20
H2003R1030101A	4.00	7.20
H2003R1040101A	6.00	9.20
H2003R1050101A	8.00	11.20
H2003R1060101A	10.00	13.20
H2003R1070101A	12.00	15.20
H2003R1080101A	14.00	17.20
H2003R1090101A	16.00	19.20
H2003R1100101A	18.00	21.40
H2003R1110101A	20.00	23.40
H2003R1120101A	22.00	25.40
H2003R1130101A	24.00	27.40
H2003R1140101A	26.00	29.40
H2003R1150101A	28.00	31.40
H2003R1160101A	30.00	33.40

MARK	REVISION DESCRIPTION	SIGNATURE	DATE	TOLERANCE	TITLE:	DRAWN:	CHECKED:	APPROVED:	REV.: A5	DRAWING NO.:
A5	Uniformly arrange the drawings	ZSZ	2021.09.06	X.X ±0.30	SAN2.0 90° Housing	ZSZ 2021.09.06			A5	2003HR01-A-S
A4	Change the part number and frame format	TLX	2020.03.28	X.XX ±0.20						
				X.XXX ±0.10		UNIT:mm	SCALE:N/A	SHEET:1/1	PROJECTION	
				Angle ±2°						

KONNRA 东莞市康瑞电子有限公司
DongGuan Konnra Electronics Co.,Ltd.

PART NO.: H2003R1**0101A