


| | | | | |
|-----|----------|------------------------------|------|------|
| ⑫ | Labe | 旗形标签 白底黑字 L=80 W=20 | 1 | pcs |
| ⑪ | Tube | 白色印字套管 印字内容如图所示 | 7 | pcs |
| ⑩ | Tube | 黑色热缩套管 | 1 | pcs |
| ⑨ | Core | 磁环: FJC3-F295402R | 1 | pcs |
| ⑧ | Terminal | XH2.5 带扣 Terminal/Tin plated | 4 | pcs |
| ⑦ | Housing | XH2.5 带扣 Housing 2P | 4 | pcs |
| ⑥ | Terminal | HSNB8-4-90D | 1 | pcs |
| ⑤ | Terminal | HSNB5.5-4S-90D | 2 | pcs |
| ④ | Terminal | 典威PV连接器端子 (DW411F2013B) | 2 | pcs |
| ③ | Terminal | 典威PV连接器端子 (DW411M2013) | 2 | pcs |
| ② | Wire | UL1332 22AWG OD:1.36mm 红 | 4 | pcs |
| ① | Wire | UL10269 12AWG OD:4.3mm 红/黑 | 4 | pcs |
| NO. | Material | Description | Q'TY | Unit |

标签双面印字 靠近P2端对贴

WIRE LIST

| | Color | | 长度 (mm) | Remark |
|---------|-------|---------|---------|-------------|
| P1 (合铆) | 红色 | P8-1 | 100±5 | UL1332 #22 |
| | 黑色 | P2 (合铆) | 230±10 | UL10269 #12 |
| P3 (合铆) | 黑色 | P2 (合铆) | 270±10 | UL10269 #12 |
| | 红色 | P9-1 | 100±5 | UL1332 #22 |
| P4 (合铆) | 红色 | P5 | 230±10 | UL10269 #12 |
| | 红色 | P10-1 | 100±5 | UL1332 #22 |
| P6 (合铆) | 红色 | P7 | 270±10 | UL10269 #12 |
| | 红色 | P11-1 | 100±5 | UL1332 #22 |



注意事项:
1. 100%短路, 断路, 错位测试.
2. 导通阻抗: 5Ω/Max.

| | | | | | | | | | |
|------|----------------------|-----------|------|------------------------|-----------------------|--------------------------------------|------------|---------|--------------------------|
| A4 | | | | TITLE: | DRAWN: 车忠浩 2024.09.04 | KONNRA 东莞市康瑞电子有限公司 | | | |
| A3 | | | | XH2.5/DW411 T0 | CHECKED: | DongGuan Konnra Electronics Co.,Ltd. | | | |
| A2 | | | | HSNB8-4-90D/5.5-4S-90D | APPROVED: | PART NO.:XSZ11134015 | | | |
| MARK | REVISION DESCRIPTION | SIGNATURE | DATE | UNIT:mm | SCALE:N/A | SHEET:1/1 | PROJECTION | REV.:A1 | DRAWING NO.:XSZ11134015S |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | |